

High Peaks Pressure HIGH FLEXIBILITY



Four High Tensile Spiral Hose exceeds ISO18752-CC/SAE 100R15 performance

VINCKE HH-4S

4SS +											
Code	Nominal ø		Inside ø	Braid ø	Outside ø	Max. Working Pressure	Burst Pressure	Minimum Bend Radius	Weight		
	Dash Size	inch	mm	mm	mm	bar	psi	bar	psi	mm	g/m
4S08	08	1/2"	12,7	20	22,2	420	6000	1680	24360	90	885
4S10	10	5/8"	16	24,4	26,4	420	6000	1680	24360	120	1120
4S12	12	3/4"	19	28,5	30,1	420	6000	1680	24360	150	1450
4S16	16	1"	25,4	34,6	36,6	420	6000	1680	24360	200	2015
4S20	20	1 1/4"	31	41,9	45	420	6000	1680	24360	250	3785

Construction:

Tube: seamless oil resistant synthetic rubber

Reinforcement: 4 high tensile steel spiral

Wrapped cover: weather, abrasion and ozone, resistant synthetic rubber

Fluid resistance: Hydraulic fluids on mineral, vegetable and synthetic oil, water based fluids.

Temperature range: -40°C + 121°C Max (max 125°C discontinuous)

HOSE TESTED OVER >700.00 DYNAMIC IMPULSE CYCLES (100°C)

