


M BIR12PC BSP

Codice articolo: 805600003 / Male



Body size 1/2"	Valving style Poppet
Interchange ISO 7241 A	Sealing Nitrile NBR
Connection system Pull back the sleeve and push	Disconnection system Pull back the sleeve
Material Carbon steel	Treatment Cr3
Locking mechanism Locking ball	Disconnectable under pressure No
Thread FEMALE THREAD BSPP (ISO 1179-1)	Connectable under residual pressure Pressure in one side
Temperature -20 / +100 °C; -4 / +212 °F	Applications Agriculture, Industry

Performance

	METRIC
ISO DN (mm)	12.5
Flow (l/min)	Da 50 a 150
Max. Flow suggested (l/min)	90
Max. Operating pressure - coupled (Mpa)	25
Operating pressure - uncoupled (mpa)	25
Burst pressure - coupled (mpa)	80
Burst pressure - uncoupled (mpa)	80
Connect force (N)	70
Disconnect force (N)	55
Spillage (ml)	2.1

Dimensions

	METRIC
Port (A)	1/2"
Overall length M+F (mm)	86,3
Length (mm)	44,5
Max. diameter (mm)	20,5
Weight (kg)	0,08

Related products




Product code	Type	Product name
805600002	Femmina	F BIR12PC BSP

Spare kits

Product code	Product name
815515003	PARKING STATION FOR M ISOA 12
815515005	PARKING STATION PLASTIC FOR M ISOA 12

F BIR12PC BSP

Codice articolo: 805600002 / Female



Body size 1/2"	Valving style Poppet
Interchange ISO 7241 A	Sealing Nitrile NBR
Connection system Pull back the sleeve and push	Disconnection system Pull back the sleeve
Material Carbon steel	Treatment Cr3
Locking mechanism Locking ball	Disconnectable under pressure No
Thread FEMALE THREAD BSPP (ISO 1179-1)	Connectable under residual pressure Pressure in one side
Temperature -20 / +100 °C; -4 / +212 °F	Applications Agriculture, Industry

Performance

METRIC

ISO DN (mm)	12.5
Flow (l/min)	Da 50 a 150
Max. Flow suggested (l/min)	90
Max. Operating pressure - coupled (Mpa)	25
Operating pressure - uncoupled (mpa)	25
Burst pressure - coupled (mpa)	80
Burst pressure - uncoupled (mpa)	100
Connect force (N)	70
Disconnect force (N)	55
Spillage (ml)	2.1

Dimensions

METRIC

Port (A)	1/2"
Overall length M+F (mm)	86,3
Length (mm)	63,3
Max. diameter (mm)	38
Weight (kg)	0,25

Related products

Product code	Type	Product name
805600003	Maschio	M BIR12PC BSP

Spare kits

Product code	Product name
815700174	SPARE KIT OR NBR+BK F BIR12

Caps

Product code	Product name
815000004	PLASTIC PLUG F ISO-A/IR12 RED