


Medium / High Pressure



Two Wire Braid Hydraulic Hose meets or exceeds EN857 2SC

VINCKE HH-24S

2SC PLUS SMOOTH											
Code	Nominal ø		Inside ø	Braid ø	Outside ø	Max. Working Pressure	Burst Pressure	Minimum Bend Radius	Weight		
Dash Size	inch	mm	mm	mm	bar	psi	bar	psi	mm	g/m	
2404S	04	1/4"	6,4	11,1	13,2	420	6090	1680	24360	50	300
2405S	05	5/16"	8	12,9	15	380	5510	1520	22040	55	340
2406S	06	3/8"	9,5	15	17,1	350	5075	1400	20300	65	420
2408S	08	1/2"	12,7	18,6	20,7	310	4495	1240	17980	90	540
2410S	10	5/8"	16	21,7	23,8	280	4060	1120	16240	100	680
2412S	12	3/4"	19	25,6	27,7	270	3915	1080	15660	120	800
2416S	16	1"	25,4	33,3	35,5	185	2683	740	10730	150	1150

Construction:

Tube: seamless oil resistant synthetic rubber

Reinforcement: 2 high tensile steel wire braid

Smooth cover: weather, abrasion and ozone, resistant synthetic rubber

Fluid resistance: Hydraulic fluids on mineral, vegetable and synthetic oil, water based fluids.

Temperature range: -40°C + 100°C Max (max 120°C discontinuous)

