



Medium / High Pressure



Two Wire Braid Hydraulic Hose ISO 1307 EN857 2SC- Exceed EN857 2SC

VINCKE HH-25

2SNK SMOOTH											
Code	Nominal ø	Inside ø	Braid ø	Outside ø	Max. Working Pressure	Burst Pressure	Minimum Bend Radius	Weight			
Dash Size	inch	mm	mm	mm	bar	psi	bar	psi	mm	g/m	
2504	04	1/4"	6,4	11,1	13,2	450	6525	1950	28275	45	285
2505	05	5/16"	8	12,9	15	420	6090	1725	25012,5	60	330
2506	06	3/8"	9,5	15	17,1	385	5583	1650	23925	70	440
2508	08	1/2"	12,7	18,6	20,3	345	5003	1400	20300	90	565
2510	10	5/8"	16	21,7	23,7	290	4205	1200	17400	130	660
2512	12	3/4"	19	25,6	27,7	280	4060	1200	17400	160	835
2516	16	1"	25,4	33,3	35,5	225	3263	1000	14500	160	1370

Construction:

Tube: seamless oil resistant synthetic rubber

Reinforcement: 2 high tensile steel wire braid

Smooth cover: weather, abrasion and ozone, resistant synthetic rubber

Fluid resistance: Hydraulic fluids on mineral, vegetable and synthetic oil, water based fluids.

Temperature range: -40°C + 100°C Max (max 120°C discontinuous)

