



High Pick Pressure



VINCKE HH-33

Four/Six High Tensile Spiral Hose meets or exceeds EN 856 R13 ISO 1307

EN 856 R13											
Code	Nominal Ø		Inside Ø	Braid Ø	Outside Ø	Burst Pressure	Max. Working Pressure	Minimum Bend Radius	Weight		
	Dash Size	inch	mm	mm	mm	bar	psi	bar	psi	mm	g/m
3312	12	3/4"	19	29	32	1380	20010	345	5003	240	1465
3316	16	1"	25,4	35,1	38,4	1380	20010	345	5003	300	2035
3320	20	1 1/4"	31,8	46,3	49,3	1380	20010	345	5003	420	2385
3324	24	1 1/2"	38,1	53,7	57,3	1380	20010	345	5003	500	3185
3332	32	2"	50,8	68	71,6	1380	20010	345	5003	630	4365



Construction: Tube: seamless oil resistant synthetic rubber

Reinforcement: 4/6 high Tensile steel spiral

Wrapped cover: weather, abrasion and ozone, resistant synthetic rubber

Fluid resistance: Hydraulic fluids on mineral, vegetable and synthetic oil, water based fluids.

Temperature range: -40°C + 100°C Max (max 120°C intermittent)



High Pick Pressure



VINCKE HH-42

Four/Six High Tensile Spiral Hose meets or exceeds EN 856 R15 ISO 1307

R15											
Code	Nominal Ø		Inside Ø	Braid Ø	Outside Ø	Burst Pressure	Max. Working Pressure	Minimum Bend Radius	Weight		
	Dash Size	inch	mm	mm	mm	bar	psi	bar	psi	mm	g/m
42012	12	3/4"	19	28,2	32	1680	24360	420	6090	265	1465
42016	16	1"	25,4	35,1	38,4	1680	24360	420	6090	330	2035
42020	20	1 1/4"	31,8	46,3	49,3	1680	24360	420	6090	445	3815
42024	24	1 1/2"	38,1	53,7	57,3	1680	24360	420	6090	530	4770
42032	32	2"	50,8	68,4	72	1680	24360	420	6090	600	6455



Construction: Tube: seamless oil resistant synthetic rubber

Reinforcement: 4/6 high Tensile steel spiral

Wrapped cover: weather, abrasion and ozone, resistant synthetic rubber

Fluid resistance: Hydraulic fluids on mineral, vegetable and synthetic oil, water based fluids.

Temperature range: -40°C + 100°C Max (max 120°C intermittent)