



# High pressure / Micro hose Hydraulic

VINCKE TH-007

| SAE 100R7 DIN<br>EN ISO 3949 |          |       |  |  |  |  |  |  |     |    |
|------------------------------|----------|-------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-----|----|
| Code                         | Nominalø |       | Inside ø                                                                          | Outside ø                                                                         | Max. Working Pressure                                                             | Burst Pressure                                                                      | Minimum Bend Radius                                                                 | Weight                                                                              |     |    |
| Dash Size                    | inch     | mm    | mm                                                                                | bar                                                                               | psi                                                                               | bar                                                                                 | psi                                                                                 | mm                                                                                  | g/m |    |
| 00702                        | 02       | 1/12" | 2,1                                                                               | 5                                                                                 | 630                                                                               | 9135                                                                                | 1890                                                                                | 27405                                                                               | 20  | 24 |

Construction:  
 Internal core thermoplastic polyester  
 Reinforcement one braid of aramid fiber  
 Temperature Range: Continuous: -40°C to +100°C

