

Low / Medium Pressure



One Wire Braid Hydraulic Hose meets or exceeds DIN EN 853 1 SN, SAE 100R1 AT and ISO 1436

VINCKE HH-11

1SN											
Code	Nominal ø		Inside ø	Braid ø	Outside ø	Max. Working Pressure		Burst Pressure		Minimum Bend Radius	Weight
	Dash Size	inch	mm	mm	mm	bar	psi	bar	psi	mm	g/m
1103	03	3/16"	4,8	9,6	11,8	250	3625	1000	14500	90	180
1104	04	1/4"	6,4	11,1	13,4	225	3263	900	13050	100	220
1105	05	5/16"	8	12,6	15	215	3118	860	12470	115	260
1106	06	3/8"	9,5	15	17,4	180	2610	720	10440	130	330
1108	08	1/2"	12,7	18,1	20,6	160	2320	640	9280	180	410
1110	10	5/8"	16	21,2	23,7	130	1885	520	7540	200	470
1112	12	3/4"	19	25,2	27,7	105	1523	420	6090	240	585
1116	16	1"	25,4	33,1	35,6	88	1276	352	5104	300	870
1120	20	1 1/4"	31,8	40,2	43,5	63	914	252	3654	420	1205
1124	24	1 1/2"	38,1	46,7	51	50	725	200	2900	500	1400
1132	32	2"	50,8	60,2	64,5	40	580	160	2320	630	1910
1140	40	2 1/2"	63,5	73	76,5	40	580	160	2320	762	2535
1148	48	3"	76,2	85	88,5	35	508	140	2030	900	2710

