

LOW/ MEDIUM PRESSURE



One Compact Wire Braid Hydraulic Hose meets or exceeds EN 857 1 SC

VINCKE HH-17S

1SC SMOOTH											
Code	Nominal Ø		Inside Ø	Braid Ø	Outside Ø	Max. Working Pressure		Burst Pressure		Minimum Bend Radius	Weight
	Dash Size	inch	mm	mm	mm	bar	psi	bar	psi	mm	g/m
1704S	04	1/4"	6,4	10,4	12,2	225	3263	900	13050	50	180
1705S	05	5/16"	8	11,5	13,6	215	3118	860	12470	55	200
1706S	06	3/8"	9,5	13,6	15,5	180	2610	720	10440	60	260
1708S	08	1/2"	12,7	17	19	160	2320	640	9280	70	345
1710S	10	5/8"	16	20,4	22,4	130	1885	520	7540	90	420
1712S	12	3/4"	19	23,8	25,8	105	1523	420	6090	97	495
1716S	16	1"	25,4	31,3	33,4	88	1276	355	5100	150	735

Construction:

Tube: seamless oil resistant synthetic rubber

Reinforcement: 1 high tensile steel wire braid.

Smoother cover: Weather, abrasion and ozone, resistant synthetic rubber.

Fluid resistance: Hydraulic fluids on mineral, vegetable and synthetic oil, water based fluids.

Temperature range: -40°C + 100°C Max (max 120°C discontinuous).

