


Anschlüsse für MCS-Mikroschlauch

Fittings for MCS micro-hose

Hülse Ferrule



Schlauchart hose type

6400

Part. No.	L	d
800.00.002.00	14	8
800.20.002.11*	14	8


* = Edelstahl

* = stainless steel

6500 - 6700

Part. No.	L	d
800.00.004.00	21	11
/	/	/

Schraubanschluss Nut connection



Schlauchart hose type

6400

Part. No.	L	d1	p max.
801.10.161.00	22	M16x1,5	630 bar
801.10.162.00	22	M16x2	630 bar
801.11.162.00*	22	M16x2	630 bar


* = Edelstahl

* = stainless steel

6500 - 6700

Part. No.	L	d1	p max.
804.10.162.00	24	M16x2	500 bar
/	/	/	/

Steckanschluss Plug-in connection



Schlauchart hose type


6400

Part. No.	L	d	p max.
801.20.000.00	19	3,3	400 bar

a 800.02.000.01

Staubschutzkappe Dust protection cap

Rohrstutzen Standpipe



Schlauchart hose type


6400

Part. No.	L	d
801.30.004.00	26	4
801.30.006.00	26	6
801.30.008.00	26	8

6500 - 6700

Part. No.	L	d
804.30.004.00	29	4
804.30.006.00	29	6
804.30.008.00	29	8

Rohrstutzen mit Überwurfmutter + Schneidring Standpipe with nut



Schlauchart hose type

6400 - 6500

6400

Part. No.	L	d	p max.
801.31.006.00	26	6	315 bar
801.32.006.00	26	6	630 bar
801.31.008.00	26	8	315 bar
801.32.006.00	26	8	630 bar

6700

Ch.	d1
14	M12x1,5
17	M14x1,5
19	M16x1,5

6500 - 6700

Part. no	L	d	p max.
804.31.006.00	29	6	315 bar
804.32.006.00	29	6	500 bar
804.31.008.00	29	8	315 bar
804.32.008.00	29	8	500 bar